Non - rotating WIRE ROPES

35(W) x 7



Regular nominal diameter	Approx. weight	Minimum breaking load [kN]	
		1770	1960
[mm]	[Kg/m]	[N/mm²]	
10	0.452	63.7	70.6
11	0.530	77.1	85.4
12	0.628	91.8	102
13	0.742	108	119
14	0.856	125	138
15	0.988	143	159
16	1.119	163	181
18	1.418	206	229
19	1.587	230	255
20	1.752	255	282
21	1.940	281	311
22	2.122	308	342
24	2.527	367	406
26	2.949	431	477
28	3.442	500	553
30	3.933	573	635
32	4.510	652	723
34	5.058	737	816
36	5.673	826	914
38	6.324	920	1,020
40	7.095	1,020	1,130

TECHNICAL DATA:

Total number of strands: 35
Total number of wires: 245
Core type : WSC
Outer strands construction: 1 – 6
Outer strands number: 16
Lay type: regular lay
Lay direction: right hand lay

Multi strand, SUPERFLEX, non-rotating wire rope with good corrosion resistance. Used on cranes or for hoisting.

ON REQUEST OPTIONS:

Galvanized / ungalvanized
Lang lay type
Left hand lay
Greasing level
Standard: EN, ISO, DIN

For order please contact:

Tel : +40 244 598052
Fax : +40 244 598632
info@cablul-romanesc.ro
www.cablul-romanesc.ro

CABLUL ROMÂNESC

PLOIEŞTI – ROMÂNIA

Certified by:

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....